

Package: mrapi (via r-universe)

October 22, 2026

Title Machine-Readable Data Analysis Results with Function Wrappers

Version 1.0.1

Description You can use the set of wrappers for analytical schemata to reduce the effort in writing machine-readable data. The set of all-in-one wrappers will cover widely used functions from data analysis packages.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

URL <https://gitlab.com/TIBHannover/lki/knowledge-loom/mrap-r>

BugReports <https://gitlab.com/TIBHannover/lki/knowledge-loom/mrap-r/-/issues>

Imports dtreg, jsonlite, stringr

Suggests knitr, lme4, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

Config/pak/sysreqs libicu-dev libssl-dev

Repository <https://tibhannover.r-universe.dev>

Date/Publication 2025-12-07 18:54:59 UTC

RemoteUrl <https://gitlab.com/tibhannover/lki/knowledge-loom/mrap-r>

RemoteRef HEAD

RemoteSha 79f559fdbb2de62705d7b070740b70ffa4ef0e2b

Contents

algorithm_evaluation	2
class_discovery	3
class_prediction	3
correlation_analysis	4

data_analysis	5
descriptive_statistics	5
factor_analysis	6
group_comparison	7
multilevel_analysis	7
regression_analysis	8
stats_aov	9
to_jsonld	9
Index	11

algorithm_evaluation	Create an algorithm_evaluation instance
----------------------	---

Description

Create an algorithm_evaluation instance

Usage

algorithm_evaluation(code_string, input_data, named_list_results)

Arguments

- code_string A line of code as a string, or "N/A" if not given
- input_data A data frame, a named list, or a URL as a string
- named_list_results
 A named list with metrics and values

Value

An algorithm_evaluation instance

Examples

```
res <- list(F1= 0.46, recall = 0.51)
inst_ae <- algorithm_evaluation("N/A", "data_url", res)
```

class_discovery	Create a class_discovery instance
-----------------	-----------------------------------

Description

Create a class_discovery instance

Usage

```
class_discovery(code_string, input_data, test_results)
```

Arguments

code_string	A line of code as a string, or "N/A" if not given
input_data	A data frame, a named list, or a URL as a string
test_results	A data frame or a list of data frames

Value

A class_discovery instance

Examples

```
clust_data <- iris[-5]
res <- data.frame(result_1 = 1, result_2 = 2)
inst_cd <- class_discovery(
  "stats::kmeans(clust_data, 3)",
  iris,
  res
)
```

class_prediction	Create a class_prediction instance
------------------	------------------------------------

Description

Create a class_prediction instance

Usage

```
class_prediction(code_string, input_data, test_results)
```

Arguments

code_string	A line of code as a string, or "N/A" if not given
input_data	A data frame, a named list, or a URL as a string
test_results	A data frame or a list of data frames

Value

A class_prediction instance

Examples

```
res <- data.frame(result_1 = 1, result_2 = 2)
inst_cp <- class_prediction(
  "stats::glm(Species ~ Petal.Width + Petal.Length, family='binomial', iris)",
  iris,
  res
)
```

correlation_analysis *Create a correlation_analysis instance*

Description

Create a correlation_analysis instance

Usage

```
correlation_analysis(code_string, input_data, test_results)
```

Arguments

code_string	A line of code as a string, or "N/A" if not given
input_data	A data frame, a named list, or a URL as a string
test_results	A data frame or a list of data frames

Value

A correlation_analysis instance

Examples

```
res <- data.frame(result_1 = 1, result_2 = 2)
inst_ca <- correlation_analysis(
  "stats::cor.test(iris$Petal.Length, iris$Sepal.Length)",
  iris,
  res
)
```

data_analysis	Create a data_analysis instance
---------------	---------------------------------

Description

Create a data_analysis instance

Usage

```
data_analysis(instances, code_reference = NULL)
```

Arguments

instances Analytic instance or a list of instances
code_reference A URL of the code implementing data analysis

Value

A data analysis instance

Examples

```
res <- data.frame(mean = 3.758)
inst_ds <- descriptive_statistics(
  "base::mean(iris$Petal.Length)",
  iris,
  res
)
inst_da <- data_analysis(inst_ds)
```

descriptive_statistics	Create a descriptive_statistics instance
------------------------	--

Description

Create a descriptive_statistics instance

Usage

```
descriptive_statistics(code_string, input_data, test_results)
```

Arguments

code_string A line of code as a string, or "N/A" if not given
input_data A data frame, a named list, or a URL as a string
test_results A data frame or a list of data frames

Value

A descriptive_statistics instance

Examples

```
res <- data.frame(mean = 3.758)
inst_ds <- descriptive_statistics(
  "base::mean(iris$Petal.Length)",
  iris,
  res
)
```

factor_analysis	Create a factor_analysis instance
-----------------	-----------------------------------

Description

Create a factor_analysis instance

Usage

```
factor_analysis(code_string, input_data, test_results)
```

Arguments

code_string	A line of code as a string, or "N/A" if not given
input_data	A data frame, a named list, or a URL as a string
test_results	A data frame or a list of data frames

Value

A factor_analysis instance

Examples

```
fa_data <- iris[-5]
res <- data.frame(result_1 = 1, result_2 = 2)
inst_fa <- factor_analysis(
  "stats::princomp(fa_data)",
  iris,
  res
)
```

group_comparison	Create a group_comparison instance
------------------	------------------------------------

Description

Create a group_comparison instance

Usage

```
group_comparison(code_string, input_data, test_results)
```

Arguments

code_string	A line of code as a string, or "N/A" if not given
input_data	A data frame, a named list, or a URL as a string
test_results	A data frame or a list of data frames

Value

A group_comparison instance

Examples

```
res <- data.frame(result_1 = 1, result_2 = 2)
inst_gc <- group_comparison(
  "stats::aov(Petal.Length ~ Species, data = iris)",
  iris,
  res
)
```

multilevel_analysis	Create a multilevel_analysis instance
---------------------	---------------------------------------

Description

Create a multilevel_analysis instance

Usage

```
multilevel_analysis(code_string, input_data, test_results)
```

Arguments

code_string	A line of code as a string, or "N/A" if not given
input_data	A data frame, a named list, or a URL as a string
test_results	A data frame or a list of data frames

Value

A multilevel_analysis instance

Examples

```
code_string <- "lme4::lmer(math ~ homework + (1 | schid))"
res <- data.frame(result_1 = 1, result_2 = 2)
inst <- multilevel_analysis(code_string, "data_url", res)
```

regression_analysis	Create a regression_analysis instance
---------------------	---------------------------------------

Description

Create a regression_analysis instance

Usage

```
regression_analysis(code_string, input_data, test_results)
```

Arguments

code_string	A line of code as a string, or "N/A" if not given
input_data	A data frame, a named list, or a URL as a string
test_results	A data frame or a list of data frames

Value

A regression_analysis instance

Examples

```
res <- data.frame(result_1 = 1, result_2 = 2)
inst_ra <- regression_analysis(
  "stats::lm(Petal.Length ~ Sepal.Length, data = iris)",
  iris,
  res
)
```

stats_aov	<i>Wrap stats::aov function</i>
-----------	---------------------------------

Description

Wrap stats::aov function

Usage

```
stats_aov(...)
```

Arguments

... the same arguments as in the wrapped function

Value

a list of ANOVA object and R6 class instance

Examples

```
results <- stats_aov(Petal.Length ~ Species, data = iris)
```

to_jsonld	<i>Write an instance in JSON-LD format</i>
-----------	--

Description

This function is imported from dtreg for ease-of-use

Usage

```
to_jsonld(instance)
```

Arguments

instance An instance of an R6 class

Value

JSON string in JSON-LD format

Examples

```
res <- data.frame(mean = 3.758)
inst_ds <- descriptive_statistics(
  "base::mean(iris$Petal.Length)",
  iris,
  res
)
json <- to_jsonld(inst_ds)
```

Index

algorithm_evaluation, [2](#)
class_discovery, [3](#)
class_prediction, [3](#)
correlation_analysis, [4](#)
data_analysis, [5](#)
descriptive_statistics, [5](#)
factor_analysis, [6](#)
group_comparison, [7](#)
multilevel_analysis, [7](#)
regression_analysis, [8](#)
stats_aov, [9](#)
to_jsonld, [9](#)